

# FLECK 2850

## DESCRIPTION

2850 is a lead-free brass valve with environmental protective cover for water resistance, corrosion resistance, and UV stability. Designed for single or multiple tank systems ideally suitable for small commercial and industrial applications.



## FEATURES

- Time-tested, hydraulically-balanced piston, seal and spacer concept
- 1-1/2" top-mount control valve
- Valve body in brass
- Regeneration: electronic

## VALVE SPECIFICATIONS

Service flow rate	11.6 m <sup>3</sup> /hr
Backwash flow rate	11.1 m <sup>3</sup> /hr
Operating pressure	1.4 to 8.5 bar
Water temperature	1°C to 43°C
Valve material	Brass
In/out	1 1/2 inch
Type timer	SXT
Hot water	No

\*3.5 bar inlet - valve alone

# FLECK 2850



## ELECTRONIC VALVES & METERS\*

REFERENCE	CONFIG	SEARCH NAME	ITEM NAME
0301280100	CSXD	V285SC-602	Fleck 2850/1650 SXT   Chrono SXT Down Flow   3/5/1
0301280100	CSXD-NB	V285SC-603	Fleck 2850/1650 SXT   Chrono SXT Down Flow NBP   3/5/1
0301280099	CSXD	V285SC-605	Fleck 2850/1710 SXT   Chrono SXT Down Flow   4C/10/2
0301280099	CSXD-NB	V285SC-606	Fleck 2850/1710 SXT   Chrono SXT Down Flow NBP   4C/10/2

### Electronic Meters

0401150023	29097	Kit 1" 1/2 Meter NXT Stainless Steel
------------	-------	--------------------------------------

\*Electronic versions: meter to be ordered separately

## FILTER VALVES & DLFC'S\*

REFERENCE	CONFIG	SEARCH NAME	ITEM NAME
0301283093	SXT	V285SC-600	Fleck 2850 Filter   Chrono SXT - no DLFC
0301283093	SXT-NB	V285SC-601	Fleck 2850 Filter   Chrono SXT NBP - no DLFC

### DLFC's

0401036508	25171*	DLFC 1" NPT - 3/4" BSP Assy 1.2 - 7 GPM 2850/2910/9500
0401036510	25581	DLFC 1" NPT - 3/4" BSP Assy 9 - 25GPM 2850/2910/9500

\*Filter versions: DLFC to be ordered separately

All valves are equipped with a transformer and top distributor  
Aircheck / Distributor tube and bottom distributor are not included in the prices and must be ordered separately.