

FLECK 2910

DESCRIPTION

2910 is a lead-free brass valve for superior strength with improved 2 piston-system technology to drive independent flows of service and regeneration. Ideal for industrial applications and multivalve systems.



FEATURES

- Designed for single or multi-tank systems, alternating or interlocking
- Improved 2 piston-system technology
- Valve body in brass
- Regeneration: electrical

VALVE SPECIFICATIONS

Service flow rate	24 m ³ /hr
Backwash flow rate	7.9 m ³ /hr
Operating pressure	1.4 to 8.5 bar
Water temperature	1°C to 43°C
Valve material	Brass
In/out	2 inch
Type timer	SXT/NXT2/EWS
Hot water	NXT2

*3.5 bar inlet - valve alone

FLECK 2910



MECHANICAL VALVES

REFERENCE	CONFIG	SEARCH NAME	ITEM NAME
0301291213	NT-NB02	V291XC-601	Fleck 2910/1650 Less Timer NBP 3/7/1
0301291214	NT-NB04	V291XC-606	Fleck 2910/1710 Less Timer, Less Transfo NBP 4C/15/2

ELECTRONIC VALVES & METERS*

REFERENCE	CONFIG	SEARCH NAME	ITEM NAME
0301298455	NBP	V291NC-600	Fleck 2910/1650 NXT2 Chrono NXT2 Down Flow NBP 3/7/1
0301298456	NXTD-NBP	V291NC-603	Fleck 2910/1710 NXT2 Chrono NXT2 Down Flow 4C/15/2

Electronic Meters

0401150024	29098	Kit 2" Meter NXT Stainless Steel
------------	-------	----------------------------------

*Electronic versions: meter to be ordered separately

METER CABLES

REFERENCE	CONFIG	SEARCH NAME	ITEM NAME
0401150002		V291NC-600	Electronic meter cable 0.47m (5 pc)
0401110009		V291SC-603	Kit communication cable NXT/NXT2

All valves are equipped with a transformer and top distributor
Aircheck / Distributor tube and bottom distributor are not included in the prices and must be ordered separately.