

FLECK 3900

DESCRIPTION

3900 is a lead-free brass valve with fully adjustable 3- or 5-cycle control for an efficient and reliable water treatment. Its backwash capabilities accommodate softener tanks up to 63" and filter up to 42" in diameter. Moreover, the 3900 valve features an environmentally protective cover for water and corrosion resistance and UV stability.



FEATURES

- Time-tested, hydraulically-balanced piston, seal and spacer concept
- Versatile top or side mount
- Valve body in brass
- Designed for single or multi-tank systems, alternating or interlocking

VALVE SPECIFICATIONS

Service flow rate	57 m ³ /hr
Backwash flow rate	24 m ³ /hr
Operating pressure	1.4 to 8.5 bar
Water temperature	1°C to 43°C
Valve material	Brass
In/out	3 inch
Type timer	NXT2/EWS
Hot water	Yes

*3.5 bar inlet - valve alone

MECHANICAL VALVES*

REFERENCE	CONFIG	SEARCH NAME	ITEM NAME
0301390002	LT-NB04	V390XC-603	Fleck 3900/1800 Less Timer, Less Transfo NBP 7/50/10

DLFC'S & TANK ADAPTERS

REFERENCE	CONFIG	SEARCH NAME	ITEM NAME
DLFC's			
0401036509		25580	DLFC 2" BSP - 2" BSP assy 20 - 100 GPM 3150/3900
Tank adapters			
0401267576		18926	Tank Adapter 3900 Side Mount
0401267575		18925	Tank Adapter 3900 Top Mount Flanged 6"
0401267573		18041	Tank Adapter 3900 Top Mount Threaded 6"

All valves are equipped with a transformer
Distribution systems are not included in the prices and must be ordered separately.