

FLECK 9100 - TWIN

DESCRIPTION

9100 is a fiber-reinforced noryl valve for superior strength and durability. It is non-corrosive and UV-resistant, providing a continuous service flow rate of 5.4 m³/h with a backwash of 2.3 m³/h. The 9100 regenerates immediately when needed for continuous soft water, keeping system clean for optimum operating efficiency and minimum maintenance.



FEATURES

- Regenerates with soft water
- Choice of 3/4" or 1" meter
- Use of 100% of tank capacity before switching to the second tank
- Backwash capability handles up to 16" diameter tanks

VALVE SPECIFICATIONS

Service flow rate	4.00 m ³ /hr
Backwash flow rate	1.90 m ³ /hr
Operating pressure	1.4 to 8.5 bar
Water temperature	1°C to 43°C
Valve material	Noryl
In/out	3/4 inch or 1 inch
Type timer	SXT
Hot water	No

*3.5 bar inlet - valve alone

ELECTRONIC VALVES*

REFERENCE	CONFIG	SEARCH NAME	ITEM NAME
0301910104	SXT01	V910SI-601	Fleck 9100/1600 SXT Twin Duplex SXT Eco 3/4" 1/2,4/0,5
PVC connecting tubes 2nd tank adapter			
0401293079		28243-09	9100 PVC connecting tubes 2nd tank adapter - 9"
0401293080		28243-12	9100 PVC connecting tubes 2nd tank adapter - 12"
0401294490		28243-16	9100 PVC connecting tubes 2nd tank adapter - 16"

*All versions: PVC connecting tubes to be ordered separately

All valves are equipped with a transformer, top distributors, drain elbow, 2nd tank adapter
Yokes/ Bypass/ Aircheck / Distributor tube/ Bottom distributor are not included in the prices and must be ordered separately.